

POWERBOX®


S-BOX 11.1kWh

SOLAR INVERTER

MAIN PANEL

BACKUP GATEWAY

UTILITY METER



6000 cycles
at 80% DOD



1C/1C continual
charge and discharge



5 years
standard warranty



Superior LiFePO4
safety performance



Low voltage
safety connection



Max. 8 modules parallel

Features:

Two Mounting Methods:

1 Wall Mounted with Wall Bracket

2 Floor Stand With Detachable Floor Bracket

Compatible With Inverter Brands

battery BMS supports simultaneous communication and compatible with multiple inverter brands

SUN  SYNK®

 **Voltronic Power**
Advancing Power

 **victron energy**
BLUE POWER

 **Growatt**
POWERING SOLUTION

 **Deye** 德業®

 **SMA**

 **LUXPOWER**™


 **phocos**

51.2V Wall Mounted LiFePO4 Battery

5KWH 7.5KWH 10KWH 14KWH

POWERBOX[®]
S-BOX 5.12KWH

PARTIAL HOME BACKUP



Parameters

Product Model	ES-BOX12	ES-BOX12 PRO	ES-BOX12 PLUS	ES-BOX12 MAX
Nominal Energy	5.12KWH	7.68KWH	10.34KWH	14.34KWH
Nominal Voltage	51.2V	51.2V	51.2V	51.2V
Nominal Capacity	100Ah	150Ah	202Ah	280Ah
Cell Type	LFP	LFP	LFP	LFP
Standard Charge Voltage	56V	56V	56V	56V
Max Discharge Current	100A	150A	150A	200A
Discharge Cut-Off Voltage	44.8V	44.8V	44.8V	44.8V
Parallels Function	Support 8 Units In Parallels			
Communication Interface	RS485、RS232、CAN (Optional)			
Cycle Life *	≥6000 Cycles (80%DOD)			
Charge temperature range	0~65°C			
Discharge temperature range	-20~65°C			
Certification	MSDS / UN38.3			
Dimensions	480*600*150mm	480*650*180mm	480*650*225mm	480*650*225mm
Weight	58Kg	80Kg	93Kg	130Kg
Installation method	Wall Mounted/Floor Standing			
Warranty	10 Years(under warranty terms)			

*Test Condition: 80% DOD, 0.2C charge & discharge @25°C


51.2V Wall Mounted LiFePO4 Battery

5KWH 7.5KWH 10KWH 14KWH


POWERBOX[®]
51.2V 14KWH

● Different current/Temperature Discharge curves

Different Rate Discharge Curve @25°C




Different Temperature Discharge Curve @0.5C




● Charging and Discharge curve

Charge and Discharge at 25°C, 0.5C




Different Temperature Self Discharge Curve



● Cycle Life Curve

Different Discharge Depth Life Curves & 25°C, 0.5C



Different Discharge Depth Life Curves & 40°C, 0.5C

